SAFETY DATA SHEET - Red Back Jointing Tube Paste

AQUARIUS RUBBER (AUST) PTY LTD

Trading as Aquarius Distribution

ABN 79 502 567 531 PO Box 9060 Scoresby Australia 3179

Victoria

46 Rushdale Street Knoxfield Victoria Australia 3180 Telephone: 03 9763 0044 Facsimile: 03 9764 1266

E-mail: admin@aquariusdist.com.au Web-Site: http://www.aquariusdist.com.au

Date of issue: 1st July 2006

Non Hazardous according to criteria of Worksafe Australia

IDENTIFICATION:

Product Code Red408

Product Name Red Back Wonder Juice Thread Sealant Red Back Wonder Juice Thread Sealant Other Names:

Barcode Number 9326415004084 **Dangerous Goods Class** None allocated **Hazchem Code** None allocated **Poisons Schedule** Not scheduled

Product Use Thread sealant for use on metal threads containing either

gas or water

PHYSICAL DATA:

Appearance Yellow liquid

Melting Point Boiling Point =150°C Flash Point =95°C **Specific Gravity** 1.06

Solubility in water Solved in organic solvent. Solved in water slightly

Characteristic Flammable Limit LEL Not available

COMPOSITION INFORMATION

CAS Proportion% Chemical name:

30-80 25852-47-5 Polyglycol dimethacrylate Polyglycol 400 Monolaurate 9004-96-0 10-30 80-15-9 10-10 Cumene hydroperoxide Saccharin 81-07-2 1-5 **Amorphous fume Silica** 68611-44-9 1-5

HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

Swallowed May be harmful if swallowed

Contact with eyes will cause irritation, stimulation, Eye

rubefaction, weeping eyes, faintness

Skin Moderate skin irritation. May cause allergic skin reaction Inhaled May cause respiratory tract, nose and breath stimulation,

dazed, weakness, tiredness, surfeit, headache, and

possible lose of consciousness

FIRST AID:

Skin

Swallowed If swallowed, **DO NOT** induce vomiting. Immediately seek

medical advice or contact the Poisons Information Centre.

Eye Open eyes and rinse for at least 15 minutes with plenty of flowing water. See doctor immediately.

Remove contaminated clothing and wash skin thoroughly

with soap and water. Seek medical advice if symptoms

occur.

Inhaled Remove affected person from contaminated area and

seek medical advice

First Aid Facilities Eye wash fountains and safety showers should be

available for emergency use

ADVICE TO DOCTOR:

specific antidote. Supportive care. Treat

symptomatically.

Issue Date: 23/08/06 Revision Date: 29/06/07 Page 1 of 2

SAFETY DATA SHEET - Red Back Jointing Tube Paste

PRECAUTIONS FOR USE

Exposure Limits None established

Engineering Controls Fan forced ventilation may be required where

concentrations exceed occupational exposure limits

PERSONAL PROTECTION:

Eyes: Wear safety chemical goggles/glasses

Hands/Arms: Wear chemical safety gloves

Respiratory: Good general or local exhaust ventilation required

Clothing: Wear general safety clothing

FLAMMABILITY Not flammable

SAFE HANDLING INFORMATION

STORAGE & TRANSPORT:

Dangerous Goods Class Class 3 Subsidiary risk: None

Storage Precautions For safe storage, store below 38°C keep in cool well

ventilated area away from heat, sparks, and open flame. Avoid direct sunlight, Keep container tightly closed until ready for use. Avoid contacting the strong oxidizers. Strong alkalis. Strong acid, other polymerization initiators

Transport Not classified as a dangerous good for transport by rail or

road in the Australian Dangerous Goods Code.

Spills and Disposal Ventilate area of spill. Use sand or similar material to

absorb spillage. Prevent run-off into drains and waterways. Collect the absorbed material and place it into chemical waste bin, seal them and label them in accordance with Worksafe workplace substances labelling

code.

FIRE / EXPLOSION HAZHARD:

Extinguishing Media Dry chemical, foam or carbon dioxide

Hazchem Code None allocated

Fire-Fighting Recommendations: Wear self-contained breathing apparatus and full

protective clothing, cooling the equipment with cold water

Toxicology

Estimated oral LD50: Greater than 10000mg/kg (rat)
Estimated dermal LD50: Greater than 5000mg/kg (rabbit)

OTHER INFORMATION

 CONTACT:
 Robert Bass

 Telephone:
 (03) 9763-0044

 Fax:
 (03) 9764-1266

The information in this document is given to provide details of known hazards and is prepared from sources believed reliable, and can only be used for safety and health purposes. Aquarius Rubber (Aust) Pty Ltd makes no warranty that it is in all cases correct and sufficient. Prepared along Worksafe guidelines. This material safety data sheet can only be copied in its entirety without any alterations.

Issue Date: 23/08/06 Revision Date: 29/06/07 Page 2 of 2