

# ARDEX D1

Chemwatch Material Safety Data Sheet  
Issue Date: 18-Aug-2008  
NC317ECP

CHEMWATCH 5046-59  
Version No:4  
CD 2008/2 Page 1 of 10

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

ARDEX D1

### SYNONYMS

abamastic


### PRODUCT USE

Water- based premixed wall tile adhesive for fixing ceramic tiles in interior situations.

### SUPPLIER

Company: Ardex Australia Pty Ltd  
Address:  
20 Powers Road  
Seven Hills  
NSW, 2147  
AUS  
Telephone: 1800 224 070  
Fax: +61 2 9838 7817

### CHEMWATCH HAZARD RATINGS



## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

### POISONS SCHEDULE

None

### RISK

None under normal operating conditions.

### SAFETY

Avoid exposure - obtain special instructions before use.

In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.

continued...

# ARDEX D1

Chemwatch Material Safety Data Sheet  
Issue Date: 18-Aug-2008  
NC317ECP

CHEMWATCH 5046-59  
Version No:4  
CD 2008/2 Page 2 of 10

---

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

NAME	CAS RN	%
ethylene glycol monobutyl ether	111-76-2	<0.9
biocide, unspecified		<1
non hazardous ingredients, unspecified		>60

---

## Section 4 - FIRST AID MEASURES

---

### SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

### EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
  - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
  - If pain persists or recurs seek medical attention.
  - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
  - Flush skin and hair with running water (and soap if available).
  - Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

### NOTES TO PHYSICIAN

Treat symptomatically.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

### FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered a significant fire risk, however containers may burn.

continued...

# ARDEX D1

Chemwatch Material Safety Data Sheet

Issue Date: 18-Aug-2008

NC317ECP

CHEMWATCH 5046-59

Version No:4

CD 2008/2 Page 3 of 10

Section 5 - FIRE FIGHTING MEASURES

---

Decomposition may produce toxic fumes of: carbon dioxide (CO<sub>2</sub>),  
typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

other pyrolysis products

## FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM: None

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### EMERGENCY PROCEDURES

#### MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety goggles.
- Trowel up/scrape up.
- Place spilled material in clean, dry, sealed container.
- Flush spill area with water.
- Clean up all spills immediately.
- Avoid breathing vapours/ aerosols or dusts and avoid contact with skin and eyes.
- Place in a suitable labelled container for waste disposal.

#### MAJOR SPILLS

Minor hazard.

- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

---

## Section 7 - HANDLING AND STORAGE

---

### PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.

continued...

# ARDEX D1

## Chemwatch Material Safety Data Sheet

Issue Date: 18-Aug-2008

NC317ECP

CHEMWATCH 5046-59

Version No:4

CD 2008/2 Page 4 of 10

Section 7 - HANDLING AND STORAGE

- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>
Australia Exposure Standards	ethylene glycol monobutyl ether (2-Butoxyethanol)	20	96.9	50	242

### EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m <sup>3</sup> )	Revised IDLH Value (ppm)
ethylene glycol monobutyl ether		700 [Unch]

### ODOUR SAFETY FACTOR (OSF)

OSF=2E2 (2-BUTOXY ETHANOL)

### MATERIAL DATA

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by

continued...

# ARDEX D1

Chemwatch Material Safety Data Sheet

Issue Date: 18-Aug-2008

NC317ECP

CHEMWATCH 5046-59

Version No:4

CD 2008/2 Page 5 of 10

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

B	26- 550	working activities As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

### INGREDIENT DATA

#### ETHYLENE GLYCOL MONOBUTYL ETHER:

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated. These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen  
Jankovic J., Drake F.: A Screening Method for Occupational Reproductive  
American Industrial Hygiene Association Journal 57: 641-649 (1996).

Odour Threshold Value: 0.10 ppm (detection), 0.35 ppm (recognition)

Although rats appear to be more susceptible than other animals anaemia is not uncommon amongst humans following exposure. The TLV reflects the need to maintain exposures below levels found to cause blood changes in experimental animals. It is concluded that this limit will reduce the significant risk of irritation, haematologic effects and other systemic effects observed in humans and animals exposed to higher vapour concentrations. The toxic effects typical of some other glycol ethers (pancytopenia, testis atrophy and teratogenic effects) are not found with this substance.

### PERSONAL PROTECTION

#### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC

continued...

# ARDEX D1

Chemwatch Material Safety Data Sheet

Issue Date: 18-Aug-2008

NC317ECP

CHEMWATCH 5046-59

Version No:4

CD 2008/2 Page 6 of 10

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

NIOSH Current Intelligence Bulletin 59].

### HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

### OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

### RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	A- AUS	-
1000	50	-	A- AUS
5000	50	Airline *	-
5000	100	-	A- 2
10000	100	-	A- 3
	100+		Airline**

\* - Continuous Flow

\*\* - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

## ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Thick white paste with a mild acrylic and ammonia odour; mixes with water.

### PHYSICAL PROPERTIES

Mixes with water.

Molecular Weight: Not Applicable

Boiling Range (°C): 100

continued...

# ARDEX D1

Chemwatch Material Safety Data Sheet

Issue Date: 18-Aug-2008

NC317ECP

CHEMWATCH 5046-59

Version No:4

CD 2008/2 Page 7 of 10

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Melting Range (°C): Not Available  
Solubility in water (g/L): Miscible  
pH (1% solution): Not Available  
Volatile Component (%vol): Not Available  
Relative Vapour Density (air=1): >1  
Lower Explosive Limit (%): Not Applicable  
Autoignition Temp (°C): Not Applicable  
State: Non Slump Paste

Specific Gravity (water= 1): 1.4 approx.  
pH (as supplied): 8.7- 9.2  
Vapour Pressure (kPa): Not Available  
Evaporation Rate: Not Available  
Flash Point (°C): Not Applicable  
Upper Explosive Limit (%): Not Applicable  
Decomposition Temp (°C): Not Available  
Viscosity: Not Available

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

### CONDITIONS CONTRIBUTING TO INSTABILITY

Product is considered stable and hazardous polymerisation will not occur.

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

##### EYE

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

##### SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

##### INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

#### CHRONIC HEALTH EFFECTS

There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby.

continued...

# ARDEX D1

## Chemwatch Material Safety Data Sheet

Issue Date: 18-Aug-2008

NC317ECP

CHEMWATCH 5046-59

Version No:4

CD 2008/2 Page 8 of 10

## Section 11 - TOXICOLOGICAL INFORMATION

### TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

#### ETHYLENE GLYCOL MONOBUTYL ETHER:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

#### TOXICITY

Oral (rat) LD50: 470 mg/kg

Dermal (rabbit) LD50: 220 mg/kg

Inhalation (human) TClO: 100 ppm

Inhalation (human) TClO: 195 ppm/8h \* [Union Carbide]

Inhalation (rat- male) LC50: 486 ppm \*

Inhalation (rat- female) LC50: 450 ppm \*

The material may produce severe irritation to the eye causing pronounced inflammation.

Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

NOTE: Changes in kidney, liver, spleen and lungs are observed in animals exposed to high concentrations of this substance by all routes.

#### IRRITATION

Skin (rabbit): 500 mg, open; Mild

Eye (rabbit): 100 mg/24h- Moderate

Eye (rabbit): 100 mg SEVERE

MATERIAL	CARCINOGEN	REPROTOXIN	SENSITISER	SKIN
ethylene glycol monobutyl ether	IARC:3			

#### CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: ethylene glycol monobutyl ether Category: The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.

## Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

#### ETHYLENE GLYCOL MONOBUTYL ETHER:

Fish LC50 (96hr.) (mg/l):	1490
BCF<100:	0.4
log Kow (Prager 1995):	0.83
log Kow (Sangster 1997):	0.8
Half- life Soil - High (hours):	672
Half- life Soil - Low (hours):	168
Half- life Air - High (hours):	32.8
Half- life Air - Low (hours):	3.28
Half- life Surface water - High (hours):	672
Half- life Surface water - Low (hours):	168
Half- life Ground water - High (hours):	1344
Half- life Ground water - Low (hours):	336
Aqueous biodegradation - Aerobic - High (hours):	672
Aqueous biodegradation - Aerobic - Low (hours):	168
Aqueous biodegradation - Anaerobic - High (hours):	2688
Aqueous biodegradation - Anaerobic - Low (hours):	672
Photooxidation half- life air - High (hours):	32.8
Photooxidation half- life air - Low (hours):	3.28
Fish LC50 (96hr.) (mg/l):	1250- 1650

continued...



# ARDEX D1

Chemwatch Material Safety Data Sheet

Issue Date: 18-Aug-2008

NC317ECP

CHEMWATCH 5046-59

Version No:4

CD 2008/2 Page 9 of 10

Section 12 - ECOLOGICAL INFORMATION

Daphnia magna EC50 (48hr.) (mg/l): 600- 1000

DO NOT discharge into sewer or waterways.

log Kow: 0.76-0.83

Koc: 67

Half-life (hr) air: 17

Henry's atm m<sup>3</sup> /mol: 2.08E-08

BOD 5 if unstated: 0.71

COD: 2.2

Log BCF: 0.4

Fish toxicity:

(-) 24h LD50: 983-1650 mg/L

(Fathead minnow) 96h LC50: 1700 mg/L \*\*

Invertebrate toxicity:

cell mult. inhib.91-900mg/L

(Daphnia) 48h LC50: >1000 mg/L \*\*

Bioaccumulation: not sig

Effects on algae and plankton: cell mult. inhib.35-900mg/L

Degradation Biological: rapid

processes Abiotic: no hydrol&photol,RxnOH\*

\*\* [Union Carbide]

## Section 13 - DISPOSAL CONSIDERATIONS

- Containers may still present a chemical hazard/ danger when empty.
  - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
  - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

## Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,  
IMDG

## Section 15 - REGULATORY INFORMATION

**POISONS SCHEDULE: None**

### REGULATIONS

Ardex D1 (CAS: None):  
No regulations applicable

ethylene glycol monobutyl ether (CAS: 111-76-2) is found on the following regulatory lists;

Australia Exposure Standards

Australia Hazardous Substances

Australia High Volume Industrial Chemical List (HVICL)

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix I

Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 6

GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships

continued...

# ARDEX D1

## Chemwatch Material Safety Data Sheet

Issue Date: 18-Aug-2008

NC317ECP

CHEMWATCH 5046-59

Version No:4

CD 2008/2 Page 10 of 10

Section 15 - REGULATORY INFORMATION

IMO IBC Code Chapter 17: Summary of minimum requirements  
IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances  
International Agency for Research on Cancer (IARC) Carcinogens  
OECD Representative List of High Production Volume (HPV) Chemicals

## Section 16 - OTHER INFORMATION

### REPRODUCTIVE HEALTH GUIDELINES

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
ethylene glycol monobutyl ether	3.6 mg/m <sup>3</sup>	100	D	NA	-

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive  
American Industrial Hygiene Association Journal 57: 641-649 (1996).

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 18-Aug-2008

Print Date: 18-Aug-2008