

This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

## Hazardous Substance, NON-Dangerous Goods

## 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

# Product name: Epoxy Super Strength - Part A (Resin)

Synonyms: Mancode Epoxy Super Strength - Part A (Resin), 35 mL X 6 units 311251 240311

Epoxy Super Strength - Part A (Resin), 35 mL X 12 units

Recommended use: Part A of a 2-part high strength adhesive.

Supplier: Bostik Australia Pty Ltd **Bostik New Zealand Limited** 

ABN: 79 003 893 838

**Street Address:** 51-71 High Street 19 Eastern Hutt Road

Thomastown VIC 3074 Wingate Lower Hutt Australia New Zealand

Telephone: +613 9279-9333 +644 567-5119 Facsimile: +613 9279-9342 +644 567-5412 Website: www.bostik.com.au www.bostik.co.nz

Australia - 1800 033 111 New Zealand - 0800 243 622 **Emergency telephone number:** 

## 2. HAZARDS IDENTIFICATION

## **AUSTRALIA CLASSIFICATION**

This material is hazardous according to health criteria of Safe Work Australia.

## **Hazard Category:**

Harmful Xn Χi Irritant

Risk Phrase(s):

R37: Irritating to respiratory system. R41: Risk of serious damage to eyes.

May cause sensitisation by skin contact. R43:

Possible risk of impaired fertility. Repr. Cat. 3. R62:

Safety Phrase(s):

Do not breathe vapour. S23:

S24/25: Avoid contact with skin and eyes.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection. S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Poisons Schedule (Aust): S5

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

Product name: Epoxy Super Strength - Part A (Resin) Substance Key: BOS0039602

**Issued: 6 May 2010** Version: 2.0 Page: 1 of 6



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

## **NEW ZEALAND CLASSIFICATION**

This material is hazardous according to health criteria of ERMA New Zealand

## **ERMA Group Standard:**

Construction Products (Subsidiary Hazard) Group Standard 2006; HSR002544

## **HSNO Hazard Classification**

6.5B	Substances that are contact sensitisers
6.8B	Substances that are suspected human reproductive or developmental toxicants
6.9	Respiratory tract irritant
8.3A	Substances that are corrosive to ocular tissue

## **Hazard Statement:**

H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.

#### Prevention Statement

Prevention Statement:		
P102	Keep out of reach of children.	
P103	Read label before use.	
P201	Obtain special instructions before use.	
P202	Do not handle until all safety precautions have been read and understood.	
P261	Avoid breathing vapour.	
P271	Use only outdoors or in a well-ventilated area.	
P272	Contaminated work clothing should not be allowed out of the workplace.	
P280	Wear protective clothing, gloves, eye/face protection and suitable respirator.	
P281	Use personal protective equipment as required.	

## DANGEROUS GOODS CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

# 3. COMPOSITION INFORMATION CHEMICAL ENTITY CAS NO. PROPORTION 4,4'-Isopropylidenediphenol Ingredients determined to be non-hazardous 80-05-7 Balance 100%

## 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Product name: Epoxy Super Strength - Part A (Resin) Substance Key: BOS0039602

Issued: 6 May 2010 Version: 2.0 Page: 2 of 6



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin contact:** If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital.

**Eye contact:** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Notes to physician: Treat symptomatically. Effects may be delayed.

## 5. FIRE-FIGHTING MEASURES

Specific hazards: Combustible liquid.

**Fire fighting further advice:** On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Hazchem Code: Not applicable.

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

## **6. ACCIDENTAL RELEASE MEASURES**

## **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

## **LARGE SPILLS**

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: Not applicable.

## 7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour.

Product name: Epoxy Super Strength - Part A (Resin) Substance Key: BOS0039602

Issued: 6 May 2010 Version: 2.0 Page: 3 of 6



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## National occupational exposure limits:

No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Natural ventilation should be adequate under normal use conditions.

Personal protection equipment: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using. If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Viscous clear liquid, with a slight odour.

**Solubility:** Insoluble in water.

Specific Gravity (20 °C): 1.15-1.166 **Relative Vapour Density (air=1):** N Av Vapour Pressure (20 °C): N Av Flash Point (°C): >150 Flammability Limits (%): N App **Autoignition Temperature (°C):** >300 Melting Point/Range (°C): N Av **Boiling Point/Range (°C):** >200 N App pH:

Viscosity (25°C): 12,000-14,000 cps

(Typical values only - consult specification sheet)
N Av = Not available
N App = Not applicable

## 10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Product name: Epoxy Super Strength - Part A (Resin) Substance Key: BOS0039602

Issued: 6 May 2010 Version: 2.0 Page: 4 of 6



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible Materials: Oxidising agents, acids and alkalis.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: Reacts with acids and alkalis.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

## **Acute Effects**

Inhalation: Material is irritant to mucous membranes and respiratory tract.

**Skin contact:** Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

**Eye contact:** A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

**Long Term Effects:** No information available for product.

## Acute toxicity / Chronic toxicity

No LD50 data available for the product.

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Ecotoxicity:** No information available.

Persistence and degradability: No information available.

Mobility: No information available.

## 13. DISPOSAL CONSIDERATIONS

Refer to State/Territory Land Waste Management Authority.

## 14. TRANSPORT INFORMATION

#### **ROAD AND RAIL TRANSPORT**

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Product name: Epoxy Super Strength - Part A (Resin) Substance Key: BOS0039602

Issued: 6 May 2010 Version: 2.0 Page: 5 of 6



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

#### MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

## **AIR TRANSPORT**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

## 15. REGULATORY INFORMATION

Poisons Schedule (Aust): S5

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## **16. OTHER INFORMATION**

## Literary reference

This Material Safety Data Sheet has been prepared by EIAS Pty Ltd on behalf of its client.

Reason(s) For Issue: Change in Hazardous Substance Classification

Addition of NZ Classification

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Bostik Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product name: Epoxy Super Strength - Part A (Resin) Substance Key: BOS0039602

Issued: 6 May 2010 Version: 2.0 Page: 6 of 6