

This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

## **NON-Hazardous Substance, NON-Dangerous Goods**

## 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Bostik Evo-Stik Hiflo Hot Melt Butyl Edge Sealant

**Synonyms:**Bostik Evo-Stik Hiflo Hot Melt Butyl Edge Sealant, 18 Kg

Mancode
163678

Recommended use: A hot melt insulating glass sealant.

**Supplier:** Bostik Australia Pty Ltd

**ABN:** 79 003 893 838 **Street Address:** 51-71 High Street

Thomastown VIC 3074

Australia

**Telephone:** +613 9279-9333 **Facsimile:** +613 9279-9342

Emergency telephone number: 1800 033 111

### 2. HAZARDS IDENTIFICATION

Based on available information, this material is not classified as hazardous according to criteria of ASCC Australia.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

Poisons Schedule (Aust): Not applicable

## 3. COMPOSITION INFORMATION

CHEMICAL ENTITY CAS NO. PROPORTION

Ingredients determined to be non-hazardous - 100%

100%

### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Get to a doctor or hospital quickly.

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Product name: Bostik Evo-Stik Hiflo Hot Melt Butyl Edge Sealant Substance Key: BOS0037101

Issued: 25 June 2009 Version: 1.0 Page: 1 of 5



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

**Skin contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye contact:** If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice. For burns immediately irrigate with copious quantities of water for 15 minutes. Urgently seek medical assistance.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Notes to physician: Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Specific hazards: Combustible material.

**Fire fighting further advice:** Can melt and flow in a fire situation. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Hazchem Code: Not applicable.

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

## **6. ACCIDENTAL RELEASE MEASURES**

### **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of dust. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

## LARGE SPILLS

Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Collect and seal in properly labelled containers or drums for disposal.

Dangerous Goods – Initial Emergency Response Guide No: Not applicable.

### 7. HANDLING AND STORAGE

**Handling:** Avoid eye contact and repeated or prolonged skin contact. Avoid all contact with heated glue.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for spills.

Product name: Bostik Evo-Stik Hiflo Hot Melt Butyl Edge Sealant Substance Key: BOS0037101

Issued: 25 June 2009 Version: 1.0 Page: 2 of 5



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### National occupational exposure limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC Australia).

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Natural ventilation should be adequate under normal use conditions.

Personal protection equipment: OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.

Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from heat resistant material (eg: leather) should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Black solid wax.

**Solubility:** Insoluble in water.

Specific Gravity (20 °C): 1.1 Relative Vapour Density (air=1): N Av Vapour Pressure (20 °C): N Av Flash Point (°C): N Av Flammability Limits (%): N Av **Autoignition Temperature (°C):** N Av Melting Point/Range (°C): N Av **Boiling Point/Range (°C):** N Av pH: N app Total VOC (g/Litre): N Av

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

#### 10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

Incompatible Materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

Product name: Bostik Evo-Stik Hiflo Hot Melt Butyl Edge Sealant Substance Key: BOS0037101

Issued: 25 June 2009 Version: 1.0 Page: 3 of 5



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

#### **Acute Effects**

**Inhalation:** Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes and respiratory tract, headache and nausea.

Skin contact: Exposure to molten material may cause skin burns. Contact with skin may result in irritation.

**Eye contact:** May be an eye irritant. Liquid splashes of molten glue can cause permanent damage. Exposure to the cold material may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

**Long Term Effects:** No information available for product.

### Acute toxicity / Chronic toxicity

No LD50 data available for the product.

### 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Ecotoxicity:** No information available.

Persistence and degradability: No information available.

Mobility: No information available.

## 13. DISPOSAL CONSIDERATIONS

Refer to State/Territory Land Waste Management Authority.

### 14. TRANSPORT INFORMATION

#### **ROAD AND RAIL TRANSPORT**

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

### **MARINE TRANSPORT**

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Product name: Bostik Evo-Stik Hiflo Hot Melt Butyl Edge Sealant Substance Key: BOS0037101

Issued: 25 June 2009 Version: 1.0 Page: 4 of 5



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

#### **AIR TRANSPORT**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

## 15. REGULATORY INFORMATION

Poisons Schedule (Aust): Not applicable

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

### **16. OTHER INFORMATION**

### Literary reference

This Material Safety Data Sheet has been prepared by EIAS Pty Ltd on behalf of its client.

Reason(s) For Issue: Revised

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Bostik Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product name: Bostik Evo-Stik Hiflo Hot Melt Butyl Edge Sealant Substance Key: BOS0037101

Issued: 25 June 2009 Version: 1.0 Page: 5 of 5