

This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

NON-Hazardous Substance, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Z Bond Steel Frame Glazing Putty

Synonyms:	Mancode
Z Bond Steel Frame Glazing Putty, 20 Kg	663360
Z Bond Steel Frame Glazing Putty, Sienna, 20 Kg	663350
Z Bond Steel Frame Glazing Putty, White, 1.75 Kg	663390
Z Bond Steel Frame Glazing Putty, White, 10 Kg	326313
Z Bond Steel Frame Glazing Putty, White, 20 Kg	663380
Z Bond Steel Frame Glazing Putty, White, 4.5 Kg	663400
Z Bond Steel Frame Glazing Putty, White, 400 g	663410

Recommended use: Glazing putties.

Supplier: Bostik Australia Pty Ltd

ABN: 79 003 893 838 **Street Address:** 51-71 High Street

Thomastown VIC 3074

Australia

Telephone: +613 9279-9333 **Facsimile:** +613 9279-9342

Emergency telephone number: 1800 033 111

2. HAZARDS IDENTIFICATION

This material, or some of its components, is on the List of Designated Hazardous Substances (ASCC) without risk and safety phrases. According to an assessment of health effects against the Approved Criteria for Classifying Hazardous Substances (ASCC), no risk and safety phrases are applicable.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

Poisons Schedule (Aust): Not applicable

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
Talc (Containing no asbestos fibre) Ingredients determined to be non-hazardous	14807-96-6 -	<2% Balance
		100%

Product name: Z Bond Steel Frame Glazing Putty

Substance Key: BOS0105801

Issued: 25 November 2008 Version: 1.0 Page: 1 of 6



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered.

Skin contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Notes to physician: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Specific hazards: Combustible material

Fire fighting further advice: On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable.

Product name: Z Bond Steel Frame Glazing Putty

Substance Key: BOS0105801

Issued: 25 November 2008 Version: 1.0 Page: 2 of 6



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for spills.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC Australia).

However for:

	TWA		STEL		CARCINOGEN	NOTICES
	ppm r	mg/m3	ppm	mg/m3	CATEGORY	
Talc, containing						
no-asbestos fibre	-	2.5	-	-	-	-

As published by the Australian Safety and Compensation Council (ASCC).

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (ASCC)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Use only in well ventilated areas. Natural ventilation should be adequate under normal use conditions. Keep containers closed when not in use.

Personal protection equipment: OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.

Wear overalls, safety glasses and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or reusing.

Product name: Z Bond Steel Frame Glazing Putty

Substance Key: BOS0105801

Issued: 25 November 2008 Version: 1.0 Page: 3 of 6



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Non-flowing putty with linseed oil odour

Solubility: Insoluble in water

Specific Gravity (20 °C): 2.0-2.5 Relative Vapour Density (air=1): N Av Vapour Pressure (20 °C): N Av Flash Point (°C): N Av Flammability Limits (%): N App **Autoignition Temperature (°C):** N Av Melting Point/Range (°C): N App **Boiling Point/Range (°C):** N App pH: N App

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible Materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Dust generated when cured putty is mechanically abraded may be an irritant to mucous membranes and respiratory tract.

Skin contact: Repeated or prolonged skin contact may lead to irritation.

Eye contact: May be an eye irritant.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Long Term Effects: No information available for product.

Acute toxicity / Chronic toxicity
No LD50 data available for the product.

Product name: Z Bond Steel Frame Glazing Putty

Substance Key: BOS0105801

Issued: 25 November 2008 Version: 1.0 Page: 4 of 6



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways. No data available for the product. However, for the constituent:

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Refer to State/Territory Land Waste Management Authority.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

Poisons Schedule (Aust): Not applicable

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Literary reference

This Material Safety Data Sheet has been prepared by EIAS Pty Ltd on behalf of its client.

Reason(s) For Issue: First Issue

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

Product name: Z Bond Steel Frame Glazing Putty

Substance Key: BOS0105801

Issued: 25 November 2008 Version: 1.0 Page: 5 of 6



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Bostik Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product name: Z Bond Steel Frame Glazing Putty

Substance Key: BOS0105801

Issued: 25 November 2008 Version: 1.0 Page: 6 of 6