MATERIAL SAFETY DATA SHEET

STATEMENT OF HAZARDOUS NATURE: 'Not classified as hazardous according to criteria

of Worksafe Australia'

CANDAN INDUSTRIES PTY LTD

65 Chetwynd street,

LOGANHOLME, Qld. 4129

A.C.N. 010 601 895

Telephone: 61 7 3209 8733 Fax: 61 7 3209 8744

Emergency telephone No. (A/H): 61 7 5574 8205

IDENTIFICATION

Product Name: LANOX mx4

Product Codes: 00101 - 300g AEROSOL

00102 - 5 Litre 00103 - 20 Litre 205 Litre

NON-AEROSOL AEROSOL

UN Number: None established UN 1950 DG Class: Not applicable Class 2.1 Hazchem Code: None established 3

Poisons Schedule: None established

Use: Heavy Duty - Anti-corrosion - Lanolin Based Lubricant.

PHYSICAL DESCRIPTION/PROPERTIES

Appearance: Tan liquid Pour Point: -26°C

Flashpoint: NON-AEROSOL AEROSOL

179°C HIGHLY FLAMMABLE - Contents under pressure.

179°C when propellant gas has dissipated

Date: 15 March 2007

Specify Gravity: .8461

Flammability Limits: LEL - Not known

UEL - Not known

Dielectric: 26

Solubility in Water: Negligible

INGREDIENTS

NON-AEROSOL

Chemical NameCAS NumberProportionLiquid hydrocarbons64742-88-7<10%</td>'Ingredients determined not to hazardous'->60%

AEROSOL

 Butane
 106-97-8
 24%

 Propane
 74-98-6
 6%

 Liquid Hydrocarbons
 64742-88-7
 <10%</td>

 Ingredients determined not
 >60%

to be hazardous'

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Halogens: None
Carcinogens: None
Threshold limit value: Not known

ACUTE

Swallowed: May cause stomach upset.

Eyes: Mild irritant.
Skin: Non irritant.

Inhaled: Inhalation of mist and aerosols may produce respiratory irritation and coughing.

Inhalation of high concentrations may lead to respiratory collapse.

Chronic: Repeated or prolonged exposure may cause dermatitis.

FIRST AID 2.

Swallowed: Do not induce vomiting, give 1 to 2 glasses of water to drink. Seek medical help.

Eyes: Irrigate thoroughly with water, if irritation occurs, seek medical advice.

Skin: Wash area with soap and water. Remove contaminated clothing and launder

before re-use.

Isolation: Remove from further exposure. If irritation, dizziness, nausea or unconsciousness

occurs, get medical assistance. Use mouth to mouth resuscitation if breathing

has stopped.

ADVICE TO DOCTOR

Treat accordingly as for conditions that might arise with the use of lanolin & mineral oil based products.

PRECAUTIONS FOR USE

EXPOSURE STANDARDS

Eyes: Very mild irritant - normal industrial eye protection practices should be employed.

Skin: Non irritant - follow standard worksafe practices.

respiratory: No special requirements under ordinary conditions of use and with adequate

ventilation.

Ventilation: Use in well ventilated areas.

Flammability: Combustible liquid. Not considered to be a significant fire risk.

SAFE HANDLING INFORMATION

STORAGE AND TRANSPORT

NON-AEROSOL: Not defined as dangerous goods under the Australian Code for the Transport of Dangerous Goods for Road and Rail. Store away from sources of heat and ignition. Keep containers closed at all times. Store undercover and out of the weather.

AEROSOL: Aerosol packs are defined as dangerous goods under the Australian Code for the Transport of Dangerous Goods for Road and Rail.

UN 1950 DG Class 2.1 Hazchem Code 3.

Do not store at temperatures over 50 °C. Do not puncture or incinerate can even empty. Do not store in direct sunlight for prolonged periods. Store undercover and out of the weather.

SPILLS

Absorb with fire retardant treated sawdust, diatomaceous earth, etc. Use appropriate waste disposal facilities in accordance with current applicable laws or regulations.

Do not allow spills to enter drains or waterways.

EXTINGUISHING MEDIA

Foam, carbon dioxide and dry chemical powder.

FIRE/EXPLOSION HAZARD

Special Fire Fighting procedures: NON AEROSOL - None

AEROSOL - Highly flammable. Contents under pressure.

May be explosive.

Special Protective Equipment: Use self contained breathing apparatus for fire in enclosed

areas.

Unusual Fire and Explosion Hazards: None.

NFPA Hazard ID: NON AEROSOL AEROSOL TOXICITY

Health - 0 Health - 0 Contains no scheduled compounds.

Flammability - 1 Flammability - 2 Reactivity - 0 Reactivity - 0

REACTIVITY DATA

Stability: (Thermal, light, etc.) Stable.

Conditions to Avoid: Extreme heat Incompatibility: Strong oxidisers.

Hazardous Decomposition

Products: Carbon Monoxide.

Hazardous

Polymerisation: Will not occur.

CONTACT PERSON: J W Chardon - Senior Technical Officer

Ph: 61 7 3209 8733 (BH) 61 7 5574 8205 (AH)

Website: www.inox-mx3.com Email: johninox@onthenet.com.au

The information contained herein is based on data of which we are aware and believe to be correct as at the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of it's use. (MX4)