



Material Safety Data Sheet



Product Name **DRY MIXED CEMENT BLENDS**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name DRY MIXED CEMENT BLENDS
Supplier Name Cockburn Cement A.B.N. 50.008.673.470
Address PO Box 38, Hamilton Hill, WA 6963
Manufacturing Plant(s) Munster Works, Lot 242 Russell Road East, Munster, WA 6166
Kwinana Works, Leath Road, Kwinana, WA 6167
Telephone 08 9411 1000
Fax 08 9411 1150
Emergency Bus Hrs 08 9411 1000 A/Hrs 08 9411 1000
Email orders@cockburncement.com.au
Web Site <http://www.cockburncement.com.au> & www.swancement.com.au

Synonym(s) General Purpose Concrete, Rapidset, Postcrete & Mortar Packs, Drymix.

Use(s)

Concrete	Paths, mowing strips, borders, stepping-stones, light foundations, footings, slabs and lintels.
Mortar	AS3700 M3 class mortar for bricklaying and rendering.
Rapidset and Postcrete	Hole filling for fence posts and pergola posts, securing clothes-lines, letterboxes, playground equipment, garden trellis and any other non-structural elements around the home.

2. HAZARD IDENTIFICATION

THIS PRODUCT IS CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF NOHSC.

RISK PHRASES

R36/37/38 Irritating to eyes, respiratory system and skin.
R40 Limited evidence of a carcinogenic effect.
R43 May cause sensitisation by skin contact.
R48/20 Harmful : danger of serious damage to health by prolonged exposure through inhalation.

SAFETY PHRASES

S20/21 When using do not eat, drink or smoke.
S22 Do not breathe dust.
S24/25 Avoid contact with skin and eyes.
S36/37 Wear suitable protective clothing and gloves.
S38 In case of insufficient ventilation, wear suitable respiratory equipment.

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE.

UN No	None Allocated	Hazchem Code	None Allocated	Pkg Group	None Allocated
DG Class	None Allocated	Subsidiary Risk(s)	None Allocated	EPG	None Allocated

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	Conc.	CAS No.
Portland Cement	Not Available	Up to 30%	65997-15-1
High Alumina Cement	Not Available	Up to 5%	65997-16-2
Crystalline Silica (from aggregate)	Quartz SiO ₂	Up to 80%	14808-60-7
Lime (calcium hydroxide)	Ca(OH) ₂	Up to 20%	1305-62-0
Chromium (VI)	Cr ⁶⁺	< 10 ppm	18540-29-9



Material Safety Data Sheet



Product Name **DRY MIXED CEMENT BLENDS**

A. FIRST AID MEASURES

Eye	Flush thoroughly with flowing water for at least 15 minutes. Seek medical attention if symptoms persist.
Inhalation	Remove from dusty area to fresh air. If symptoms persist, seek medical attention.
Skin	Wash thoroughly with water. A shower may be required.
Ingestion	Rinse mouth and lips with water. Do not induce vomiting. Give water to drink to dilute stomach contents. If symptoms persist, seek medical attention.
Advice to Doctor	Treat symptomatically.
First Aid Facilities	Eye wash station.

Additional Information - Aggravated Medical Conditions

Inhalation	Inhalation of dust through prolonged, repeated exposure can cause bronchitis, silicosis (scarring of the lung). It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin, joints, blood vessels and internal organs) and lung cancer. Epidemiological studies have shown that smoking increases the risk of bronchitis, silicosis (scarring of the lung) and lung cancer.
Skin	Prolonged and repeated skin contact with cement in wet concrete may cause both irritant dermatitis and allergic (contact) dermatitis. The latter is due to the presence of traces of water soluble hexavalent chromium in cement.

B. FIRE FIGHTING

Flammability	Non flammable. Does not support combustion of other materials.
Fire and Explosion	Non flammable. Does not cause dust explosions.
Extinguishing	Non flammable.
Hazchem Code	None.

C. ACCIDENTAL RELEASE MEASURES

Spillage	If spilt (bulk), contact emergency services if appropriate. Wear dust-proof goggles, PVC/rubber gloves, a Class P2 respirator (where an inhalation risk exists), coveralls and rubber boots. Clear area of all unprotected personnel. Prevent spill entering drains or waterways. Collect and place in sealable containers for disposal or reuse. Avoid generating dust.
Emergency Procedures	Follow safety requirements for personal protection under Section 8 Exposure Controls/Personal Protection.



Material Safety Data Sheet



Product Name **DRY MIXED CEMENT BLENDS**

7. HANDLING AND STORAGE

Storage	Store off the floor, in the original bags in cool, dry, well ventilated area, removed from moisture, oxidising agents (eg. Hypochlorites, phosphorus oxide), acids, (eg. hydrochloric acid), ethanol, interhalogens (eg. chlorine trifluoride) and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.
Handling	General Purpose Concrete is supplied in 20 and 30kg bags. Rapid Set and Postcrete are supplied in 20, 30 & 40kg bags. Recognised local safe lifting methods should be used. Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.
Property/ Environmental	Refer to Section 13.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation	Do not inhale dust/powder. Use with adequate ventilation. Where a dust inhalation hazard exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.
Exposure Standards	CHROMIUM (VI) (18540-29-9) ES-TWA: 0.05 mg/m ³ (Chromium VI compounds) SILICA, CRYSTALLINE – QUARTZ (14808-60-7) ES-TWA: 0.1 mg/m ³ (Silica Quartz, respirable, NOHSC) ES-TWA: 0.1 mg/m ³ (QLD); 0.15 mg/m ³ (NSW) WES-TWA: 0.1 mg/m ³ PORTLAND CEMENT (65997-15-1) ES-TWA: 10 mg/m ³ Portland Cement ES-TWA: 0.05 mg/m ³ Chromium (VI) Compounds (contaminant) WES-TWA: 10 mg/m ³ CALCIUM ALUMINATE CEMENT (65997-16-2) ES-TWA: 10 mg/m ³ (total dust) GYPSUM (10101-41-4) ES-TWA: 10 mg/m ³ Inhalable dust CALCIUM CARBONATE (1317-65-3) ES-TWA: 10 mg/m ³ WES-TWA: 10 mg/m ³
PPE	Wear dust-proof goggles and rubber or PVC gloves. Where an inhalation risk exists, wear a Class P2 respirator. If there is potential for prolonged and/or excessive skin contact, wear coveralls. At high dust levels, wear a Class P3 respirator or a Powered Air Purifying Respirator (PAPR) with Class P3 Filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	A grey or off-white mixture containing finely ground materials (Portland Cement, Fly Ash, Alumina cement) and fine and coarse aggregate particles up to 10 mm nominal size.	Solubility (water)	Slight, hardens on mixing with water
Odour	Odourless	Specific Gravity	Average Approx. 2.7
pH	Approximately 12	% Volatiles	Not Available
Vapour Pressure	Not Available	Flammability	Non Flammable
Vapour Density	Not Available	Flash Point	Not Relevant
Boiling Point/Melting Point	Not Available	Upper Explosion Limit	Not Relevant
		Lower Explosion Limit	Not Relevant
Evaporation Rate	Not Available	Autoignition	Not Available
Bulk Density	Dry 1500 to 1700 kg/m ³ Compacted (cast) 2250 – 2400 kg/m ³		
Particle Size	Up to nominal 10 mm		



Material Safety Data Sheet



Product Name **DRY MIXED CEMENT BLENDS**

10. STABILITY AND REACTIVITY

Reactivity Incompatible with oxidising agents (eg hypochlorites), ethanol, acids (eg. hydrochloric acid) and interhalogens (eg chlorine trifluoride). Water contact may increase product temperature 2-3°C.

Decomposition Products May evolve toxic gases when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary Slightly corrosive. Avoid eye or skin contact or dust inhalation. This product has the potential to cause acute and chronic health effects with over exposure. Crystalline silica can cause silicosis (lung disease) with chronic over exposure, however due to low levels present and product application, adverse health effects are not anticipated. Crystalline silica and hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1).

Eye Slightly corrosive. Severe irritant upon contact with powder/dust. Over exposure may result in pain, redness, corneal burns and ulceration with possible permanent damage.

Inhalation Slightly corrosive. Over exposure may result in severe mucous membrane irritation and bronchitis. Hexavalent chromium is reported to cause respiratory sensitisation, however due to the trace amount present, a hazard is not anticipated under normal conditions of use.

Skin Slightly corrosive. Prolonged and repeated contact with powder or wetted form may result in skin rash, dermatitis and sensitisation.

Ingestion Slightly corrosive. Ingestion may result in burns to the mouth and throat, with vomiting and abdominal pain. Due to product form, ingestion is not considered a likely exposure route.

Toxicity Data SILICA, CRYSTALLINE – QUARTZ (14808-60-7)
Carcinogenicity: Classified as a human carcinogen (IARC Group 1)
CHROMIUM (VI) (18540-29-9)
Carcinogenicity: Confirmed human carcinogen (IARC Group 1)
Health Surveillance: Required [NOHSC:1005(1994)]

12. ECOLOGICAL INFORMATION

Environment Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer for additional information.

Legislation Dispose of in accordance with relevant local legislation. Keep out of sewer and stormwater drains.

14. TRANSPORT INFORMATION

Not classified as a dangerous good by the criteria of the ADG Code.

Drivers of trucks transporting bagged product should ensure that the bags are properly restrained.

Shipping Name	None Allocated				
UN No	None Allocated	Hazchem Code	None Allocated	Pkg Group	None Allocated
DG Class	None Allocated	Subsidiary Risk(s)	None Allocated	EPG	None Allocated



Material Safety Data Sheet



Product Name **DRY MIXED CEMENT BLENDS**

10. REGULATORY INFORMATION

Poison Schedule AICS A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

11. OTHER INFORMATION

Additional Information

CEMENT CONTACT DERMATITIS: Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble (hexavalent) chromium.

IARC – GROUP 1 – PROVEN HUMAN CARCINOGEN. This product contains an ingredient for which there is sufficient evidence to have been classified by the International Agency for Research into Cancer as a human carcinogen. The use of products known to be human carcinogens should be strictly monitored and controlled.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The Recommendation for protective equipment contained within this MSDS report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare an MSDS report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

ABBREVIATIONS:

mg/m³ - Milligrams per cubic metre

ppm - Parts Per Million

ES-TWA - Exposure Standard - Time Weighted Average

pH - relates to hydrogen ion concentration - this value will relate to a scale of 0 - 14, where 0 is highly acidic and 14 is highly alkaline.

CAS# - Chemical Abstract Service Number - used to uniquely identify chemical compounds.

IARC - International Agency for Research on Cancer.

WES-TWA - Workplace Exposure Standard - Time Weighted Average

Report Status

This document has been compiled by Cockburn Cement Limited the manufacturer of the product and serves as the manufacturer's Material Safety Data Sheet ("MSDS").

While Cockburn Cement Limited has taken all due care to include accurate and up-to-date information in this MSDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, Cockburn Cement Limited accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS.



Material Safety Data Sheet



Product Name **DRY MIXED CEMENT BLENDS**

Contact Point

For further information on this product contact:

Telephone: Office hours 08 9411 1000
 After hours 08 9411 1000
Facsimile: 08 9411 1150
Web site: <http://www.cockburncement.com.au>

Advice Note

The information in this document is believed to be accurate. Please check the currency of this MSDS by contacting:

08 9411 1000
or
<http://www.cockburncement.com.au> or www.swancement.com.au

The provision of this information should not be construed as a recommendation to use this product in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Users should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace and in conjunction with other substances or products.