



DuPont™ SUVA® 410A Refrigerant

Version 2.3

Revision Date 17.07.2007

Ref. 130000000570

This SDS adheres to the standards and regulatory requirements of Great Britain and may not meet the regulatory requirements in other countries.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product information

Product name : DuPont™ SUVA® 410A Refrigerant

Types : ASHRAE Refrigerant number designation: R-410A

Use of the Substance/Preparation : Refrigerant

Company : Du Pont de Nemours (Nederland) B.V.
Baanhoekweg 22
NL-3313 LA Dordrecht
The Netherlands

Telephone : +31-78-630.1011

Emergency telephone : +44-(0)8456-006.640

E-mail address : sds-support@che.dupont.com

2. HAZARDS IDENTIFICATION

Rapid evaporation of the liquid may cause frostbite.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	EC-No.	Classification	Concentration [%]
Pentafluoroethane (R125)	354-33-6	206-557-8		50
Difluoromethane (R32)	75-10-5	200-839-4	F+; R12	50

For the full text of the R phrases mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

General advice : If unconscious place in recovery position and seek medical advice. Never give anything by mouth to an unconscious person. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.

Inhalation : Move to fresh air. Keep patient warm and at rest. Artificial respiration and/or oxygen may be necessary.

Skin contact : Wash off with warm water. Take off all contaminated clothing immediately.

Eye contact : Rinse thoroughly with plenty of water, also under the eyelids. Consult a physician.



DuPont™ SUVA® 410A Refrigerant

Version 2.3

Revision Date 17.07.2007

Ref. 130000000570

Notes to physician

Treatment : Do not give adrenaline or similar drugs.

5. FIRE-FIGHTING MEASURES

Specific hazards during fire fighting : pressure build-up

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Cool containers / tanks with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Evacuate personnel to safe areas. Ventilate the area. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Should not be released into the environment.

Methods for cleaning up : Evaporates.

7. HANDLING AND STORAGE

Handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms. For personal protection see section 8.

Advice on protection against fire and explosion : No special protective measures against fire required.

Storage

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in original container.

Advice on common storage : No materials to be especially mentioned.

German storage class : 2A : Compressed, liquefied or pressurised gas

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Respiratory protection : For rescue and maintenance work in storage tanks use self-contained breathing



DuPont™ SUVA® 410A Refrigerant

Version 2.3

Revision Date 17.07.2007

Ref. 130000000570

apparatus. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

- Hand protection : Heat insulating gloves
- Eye protection : Safety glasses
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquefied gas,
- Colour : colourless,
- Odour : ether-like,
- pH : neutral
- Boiling point/boiling range : -51,6 °C at 1 013 hPa
- Flash point : does not flash
- Lower explosion limit : , not applicable
- Vapour pressure : 16 530 hPa at 25 °C
- Vapour pressure : 30 520 hPa at 50 °C
- Density : 1,062 g/cm³ at 25 °C, (as liquid)
- Density : 0,0066 g/cm³ at ca. 26 °C (1 013 hPa)

10. STABILITY AND REACTIVITY

- Materials to avoid : Alkali metals, Alkaline earth metals, Powdered metals, Powdered metal salts
- Hazardous decomposition products : Hydrogen halides, Carbon dioxide (CO₂), Carbon monoxide, Fluorocarbons, Carbonyl halides

11. TOXICOLOGICAL INFORMATION

- Acute inhalation toxicity
- Pentafluoroethane (R125) : ALC/ 4 h/ rat : > 3 480 mg/l
 - Difluoromethane (R32) : LC50/ 4 h/ rat : 2 158 mg/l
- Carcinogenicity assessment : Did not show carcinogenic effects in animal experiments.
- Toxicity to reproduction assessment : Did not show mutagenic or teratogenic effects in animal experiments.



DuPont™ SUVA® 410A Refrigerant

Version 2.3

Revision Date 17.07.2007

Ref. 130000000570

Human experience : Excessive exposures may affect human health, as follows:

Inhalation
Severe shortness of breath, narcosis, Irregular cardiac activity

Further information : Rapid evaporation of the liquid may cause frostbite.

12. ECOLOGICAL INFORMATION

Global warming potential (GWP) : 1 975

13. DISPOSAL CONSIDERATIONS

Product : Can be used after re-conditioning.

Contaminated packaging : Empty pressure vessels should be returned to the supplier.

14. TRANSPORT INFORMATION

ADR

Class: 2
 Classification Code: 2A
 HI No.: 20
 UN-Number: 1078
 Labelling No.: 2.2
 Proper shipping name: Refrigerant gas, n.o.s. (Pentafluoroethane, Difluoromethane)

IATA_C

Class: 2.2
 UN-Number: 1078
 Labelling No.: 2.2
 Proper shipping name: Refrigerant gas, n.o.s. (Pentafluoroethane, Difluoromethane)

IMDG

Class: 2.2
 UN-Number: 1078
 Labelling No.: 2.2
 Proper shipping name: Refrigerant gas, n.o.s. (Pentafluoroethane, Difluoromethane)

15. REGULATORY INFORMATION

Labelling according to EC Directives

The product does not need to be labelled in accordance with EC directives or respective national laws.

National legislation

Water contaminating class (Germany) : WGK 1 slightly water endangering



DuPont™ SUVA® 410A Refrigerant

Version 2.3

Revision Date 17.07.2007

Ref. 130000000570

16. OTHER INFORMATION

Text of R phrases mentioned in Section 3

R12 Extremely flammable.

Further information

Before use read DuPont's safety information., For further information contact the local DuPont office or DuPont's nominated distributors., ® DuPont's registered trademark

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.