



SAFETY DATA SHEET
ENAMEL SPRAY THINNER 300C

1 SUBSTANCE IDENTIFICATION AND COMPANY

PRODUCT NAME:	GALMET ENAMEL SPRAY THINNER 300C	
PRODUCT NO.	GT300C1L, GT300C4L, GT300C20L	
USE:	Paint thinner and metal cleaning solvent.	
SUPPLIER	ITW POLYMERS & FLUIDS 100 HASSALL ST WETHERILL PARK 2164 NEW SOUTH WALES AUSTRALIA T: 02 9757 8800 F: 02 9757 3855 EMERGENCY CONTACT: T: 02 9757 8800	ITW POLYMERS & FLUIDS (NZ) UNIT 2 / 38 TRUEGOOD DRIVE EAST TAMAKI, 2013 AUCKLAND NEW ZEALAND T: 09 272 1945 F: 09 273 6489 T: 09 272 1945

2 HAZARDS IDENTIFICATION

HAZARDOUS SUBSTANCE. DANGEROUS GOODS

(According to the criteria of the NOHSC and the ADG-6 code)

CLASSIFICATION	F; Highly Flammable. Xn; Harmful	
RISK PHRASES	R11	Highly Flammable.
	R20	Harmful by inhalation.
	R37	Irritating to the respiratory system.
	R65	Harmful; May cause lung damage if swallowed.
	R66	Repeated Exposure may cause skin dryness and cracking.
	R67	Vapours may cause drowsiness and dizziness.
SAFETY PHRASES	S2	Keep out of reach of children.
	S16	Keep away from sources of ignition – No Smoking.
	S23	Do not breathe vapour/spray.
	S24	Avoid contact with skin.
	S62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

3 COMPOSITION / INFORMATION ON INGREDIENTS

Name	CAS-No.	Content	Classification
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC	64742-95-6	0 - < 10 %	F; R11. Xn; R20, R37, R65, R66, R67.

4 FIRST AID MEASURES

GENERAL INFORMATION

Avoid contact with skin and eyes. Do not breathe vapour/spray. Show this safety data sheet to doctor in attendance.

INHALATION

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Contact physician if discomfort continues.

INGESTION

Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit does not enter the lungs. Get medical attention immediately!

SKIN CONTACT

Remove contaminated clothing. Wash skin thoroughly with soap and water for several minutes. Contact physician if irritation persists.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Contact physician if irritation persists.

5 FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA

Fire can be extinguished using: Alcohol resistant foam. Carbon Dioxide (CO2). Dry Chemicals.

SPECIFIC HAZARDS

Extremely flammable. Avoid breathing fire vapours. Vapour may travel considerable distance to source of ignition and flash back.

PROTECTIVE EQUIPMENT FOR FIREFIGHTERS

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SPECIAL FIRE FIGHTING PROCEDURES

Keep upwind to avoid fumes. Avoid water in straight hose stream; will scatter and spread fire. Cool containers exposed to flames with water until fire is out. Keep run-off water out of sewers and watercourses. Dike for water control. Aerosol containers may burst and become airborne missiles during fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Warn everybody of potential hazards and evacuate if necessary. Remove sources of ignition. Avoid inhalation of spray mist and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Absorb with sand or other inert absorbent. Transfer to a container for disposal. Containers with collected spillage must be properly labeled with correct contents and hazard symbol.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Take precautionary measures against static discharges. Storage tanks and other containers must be grounded. Do not smoke, use naked flames or other sources of ignition. Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.

STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place. Keep away from heat, sparks and open flame.

8 EXPOSURE CONTROL / PERSONAL PROTECTION

EXPOSURE STANDARDS

No exposure standards available for product.

Exposure standards for ingredients:

Name	TWA (LT) mg/m3	TWA (LT) ppm	STEL (ST) mg/m3	STEL (ST) ppm	Source
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC	350				Shell (2004)

PROTECTIVE EQUIPMENT (see next page)

**PROCESS CONDITIONS**

Provide eyewash, quick drench.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

RESPIRATORY EQUIPMENT

Select and use respirators in accordance with AS/NZS 1715/1716.

In poorly ventilated areas use Type A organic vapour/gas filter with half face piece.

When sanding/grinding cured product the use of a P1 dust mask (disposable) or with replaceable filters is recommended.

Filter capacity and respirator type depends on exposure levels and type of contaminant. If entering spaces where the airborne concentration of a contaminant is unknown then the use of a Self-contained breathing apparatus (SCBA) with positive pressure air supply complying with AS/NZS 1715 / 1716, or any other acceptable International Standard is recommended.

HAND PROTECTION

Use protective gloves made of: Chemical resistant gloves: e.g. Nitrile.

EYE PROTECTION

Wear safety glasses or approved chemical safety goggles where eye exposure is reasonably probable.

SKIN PROTECTION

Barrier cream, Protection suit or overalls should be worn.

HYGIENE MEASURES

Keep away from food, drink and animal feeding stuffs. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving work place.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Clear; Transparant.		
ODOUR	Solvent.		
SOLUBILITY	Not soluble in water		
BOILING POINT (°C)	95-138°C	RELATIVE DENSITY	0.78-0.81 @ 20° C
VAPOUR DENSITY (air=1)	>1	VAPOUR PRESSURE	520 kPa @ 21.1°C
EVAPORATION RATE (butyl acetate =1)	0.140	VOLATILE BY VOL. (%)	> 60 %
pH-VALUE, CONC. SOLUTION	n/a	FLASH POINT (°C)	-1°C
FLAMMABILITY LIMIT - LOWER(%)	Not known	AUTOIGNITION TEMP. (°C)	Not known
FLAMMABILITY LIMIT - UPPER(%)	Not known		

10 STABILITY & REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

MATERIALS TO AVOID

Strong oxidising agents.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire or high temperatures create: Nitrous gases (NOx). Oxides of: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

ACUTE HEALTH EFFECTS

Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication.
 Vapours may cause headache, fatigue, dizziness and nausea.
 Intentional misuse by deliberately concentrating and breathing the contents can be harmful or fatal.
 May cause lung damage if swallowed.
 May cause irritation to eyes.

CHRONIC HEALTH EFFECTS

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INGREDIENT DATA:

SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC
 TOXICITY
 Oral (rat) LD50: >2000 mg/kg

12 ECOLOGICAL INFORMATION

ECOTOXICITY

No data available, however expected to be harmful to the aquatic environment

MOBILITY

Do not discharge into drains, water courses or onto the ground.

DEGRADABILITY

No data available.

13 DISPOSAL INFORMATION

DISPOSAL METHODS

Do not puncture or incinerate can even if empty.
 Dispose of waste and residues in accordance with local authority requirements.
 Spray left over paint onto newspaper, allow to dry, and dispose newspaper in general waste. Empty steel can is recyclable. Check with your local council to see if they participate in a steel can recycling program.

14 TRANSPORT INFORMATION



ADG ROAD CLASS: 3
 PROPER SHIPPING NAME: PAINT
 UN NO. ROAD 1263
 ROAD PACK GR. II

HAZCHEM CODE	3YE	IERG (HB76: 2004)	Guide 17
IMDG CLASS	3	UN NO. SEA	1263
IMDG PAGE	NO. 3	IMDG PACK GR.	None allocated
EMS	F-D, S-U	MFAG	See Guide
MARINE POLLUTANT	Yes.		
UN NO. AIR	1263	ICAO CLASS	3

15 REGULATORY INFORMATION

SUSDP S5

RISK PHRASES IN FULL:

R11	Highly Flammable.
R20	Harmful by inhalation.
R37	Irritating to the respiratory system.
R65	Harmful; May cause lung damage if swallowed.
R66	Repeated Exposure may cause skin dryness and cracking.
R67	Vapours may cause drowsiness and dizziness.

16 OTHER INFORMATION

* The solvent in this product contains less than 0.1 % benzene, classification and labelling as a carcinogen is not required.

REVISION DATE: 4 May 2007

CONTACT: Technical Manager (02) 9757 8800

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.