Mirror Paints P/l 110 Dynon Road West Melbourne Vic 3003

Ph 03 9376 0447 Fx 03 9376 0449

MATERIAL SAFETY DATA SHEET

Date Issued: 19 October 2010

Product name Mirror – Gas Pipe Thread Sealant

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

UN number: none allocated DG class: none allocated Packing group: none allocated Hazchem code: none allocated Poisons schedule: not scheduled

Product use: This HEAVY DUTY NON HARDENING THREAD

SEALANT meets the requirements of AS 4623-2008 for use with a Class 1: gas appliance and operating pressures of up to 20 kPa. The sealant

inhibits the rusting and seizing of the joints.

Non toxic & non poisonous

PHYSICAL DATA

Appearance: Tan coloured thick paste

Melting point: not applicable Boiling point: not available Specific gravity: approx 1.6 Flash point: not applicable

Flamm. Limit LEL: not applicable Explosive data: not applicable

OTHER PROPERTIES

This is a linseed oil and mineral filler paste with additives of natural greases, wax & an anti oxidant.

Form: Thick paste

Decomposition value: not available Molecular weight: not applicable

VOCs -Volatile Component: 27 gm/litre (calculation value derived from

product formula)

MIRROR PAINTS P/L MSDS - Mirror - Gas Pipe Thread Sealant

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Acute-Swallowed: No adverse effects expected due to swallowing of small amounts incidental to industrial handling. However it is good work practice to avoid ingestion of product.

Acute-Eye: May cause slight eye irritation.

Acute-Skin: Contact with skin will result in mild irritation. Repeated or prolonged skin contact may lead to irritation.

Acute-Inhaled: No adverse effects anticipated by this route of exposure. However it is good work practise to avoid prolonged inhalation of the vapours which may cause slight irritation of nose and respiratory tract.

Chronic: No information available on this product.

FIRST AID

Swallowed: If swallowed, rinse mouth thoroughly with water. Give water, induce vomiting. Seek medical advice

EYE

If in eyes wash with flowing water for at least 15 minutes. Seek medical attention if effects persist.

Skin: Wash effected areas with copious quantities of water.

Inhaled: If effects occur remove to fresh air. Seek medical attention

ADVICE TO DOCTOR

No specific antidote. Supportive care. Treat symptomatically.

PRECAUTIONS FOR USE

Exposure limits: none established

Eng. Controls: use in well ventilated area

Other info: nil

PERSONEL PROTECTION

Protective equipment: Avoid skin and eye contact

Wear clean body- covering clothing. Use gloves that provide a water barrier and wear Safety glasses. Wash hands thoroughly before eating or drinking.

MIRROR PAINTS P/L

MSDS- Mirror - Gas Pipe Thread Sealant

Fire hazard: Non flammable

SAFE HANDLING INFORMATION

Storage and handling; Not classified as a dangerous good for transport by rail or road in the AUSTRALIAN DANGEROUS GOODS CODE. Store in a cool place out of direct sun.

Other info: Read the label instructions

EPR number: N/A

IERG number: N/A

Spills & disposal: Contain using sand and earth – prevent runoff into drains, and waterways. Prevent contamination of sewers, drains and waterways. Collect wastes and store in labelled containers for disposal. Disposal of waste materials in approved landfill. Wash residue from contaminated area with copious quantities of water.

Hazardous Reaction: Stable at normal conditions. Addition of chemicals and freezing temperatures may cause coagulations.

OTHER INFORMATION

Toxicology: no acute or chronic toxicity data available on this product. Environmental protection: no data available for this product.

Safety statement: no smoking

S24/25 avoid contact with skin and eyes.

References: 'Standards for the Uniform Scheduling of drugs and Poisons' National health and Medical Research Council as amended.

'Exposure Standards for Atmospheric Contaminates in the Occupational Environment' Worksafe Australia Standard, May 1990

Contact: Mirror paints p/l

110 Dynon road

West Melbourne Vic 3003

PH 03 9376 0447

END OF REPORT