



MATERIAL SAFETY DATA SHEET

SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: KEROSENE

Company: Recochem Inc. ABN: 69 010 485 999
Address : 1809 Lytton Road, Lytton, Queensland 4178
Phone: (07) 3308 5200 Fax: (07) 3308 5201
Emergency Telephone Number: (07) 3308 5200 Day, After Hours 1300 131 001

Other Names: Lighting Kerosene, Home Kerosene
Manufacturer's Product Code: 16000
Recommended Use: Heating fuel, Solvent, Degreasing, Fuel Oil

SECTION 2 HAZARDS IDENTIFICATION

**CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA
DANGEROUS ACCORDING TO THE CRITERIA OF THE ADG CODE**

Symbols: Xn Harmful
N Dangerous for the environment

Risk Phrases: R10 Flammable
R65 - Harmful: May cause lung damage if swallowed
R66 - Repeated exposure may cause skin dryness or cracking
R67 - Vapours may cause drowsiness and dizziness
R 51/53 Toxic to aquatic organisms, may cause long term adverse effects on the aquatic environment.
R38 - Irritating to skin.

Safety Phrases: S2 Keep out of the reach of children
S23 Do not breath vapour
S24/25 Avoid contact with skin and eyes
S61 Avoid release to the environment.
S62 If swallowed, do not induce vomiting: seek medical advice immediately and show container or label

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Material Formal Name : Naphtha (petroleum), hyrosulfurised heavy
CAS No. : 64742-82-1

Hazardous Ingredients

<i>Chemical Entity</i>	<i>CAS Number</i>	<i>Proportion (%)</i>
1,2,4-Trimethyl Benzene	95-63-6	<=10
Xylene, Mixed Isomers	1330-20-7	<=10
1,3,5-Trimethyl Benzene	203-604-4	<=10
Naphthalene	91-20-3	<=10
Contains < 0.1% w/w benzene		

SECTION 4 FIRST AID MEASURES

FIRST AID TREATMENT

Swallowed: If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Eye: If in eyes, hold eyes open, flood with water for at least 15 minutes. If redness, burning, blurred vision, or swelling persist transport to nearest medical facility for additional treatment.

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available.

Product: KEROSENE

Inhaled: Remove victim from exposure if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing

First Aid facilities: Potable water should be available to rinse eyes or skin. Provide eye baths and safety showers.

Advice to Doctor: Treat symptomatically.

Additional Information: None available.

SECTION 5 FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Foam, water spray or fog. Dry chemical powder, carbon dioxide for small fires only.
Do not use water in a jet.

Hazards from combustion products: Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. Vapour is heavier than air, can spread along ground and distant ignition is possible.

Precautions for Fire Fighters and Special Protective Equipment: Wear full protective clothing and self-contained breathing apparatus.

Additional Information: Hazchem code 3[Y]

SECTION 6 ACCIDENTAL RELEASE MEASURES

Observe all local and national regulations

Spills and Disposal: Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Remove all sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

Methods and Materials for Containment and Clean Up Procedures: For small spills (<1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow and residues to evaporate or use an appropriate absorbent material and dispose of safely.

For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow residues to evaporate or use an appropriate absorbent material and dispose of safely.

SECTION 7 HANDLING AND STORAGE

Precautions for Safe Handling and Storage: Avoid breathing of or contact with material. Use in well ventilated areas. Wash thoroughly after handling. Avoid contact with skin and eyes and clothing. Handle open containers in well ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Do not empty into drains. Do not eat, drink or smoke in contaminated areas. Before eating, drinking or smoking, remove contaminated clothing and wash hands. Do not store near strong oxidants.

Dispensing: Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment.

Flammability: Flammable

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards: HSPA(Health Systems Performance Assesment) has set an exposure standard 350mg/m³ TWA (8hr).

Biological Limit Values: No biological limit allocated

Personal Protective Equipment:

Respiratory Protection: If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter and select a filter for organic gases and vapours (boiling point > 65 Deg C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.

Hand Protection: Use solvent resistant gloves. Nitrile for longer term protection or PVC and neoprene for incidental splashes.

Eye Protection: Wear safety Goggles.

Protective Clothing: Use chemical resistant glove/gauntlets, boots and apron. Skin protection not ordinarily required beyond standard issue work clothes.

Engineering Controls: Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists. Keep containers closed when not in use.

Product: KEROSENE

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Blue Clear Liquid
Odour	Aromatic
pH:	N/A
Vapour Pressure (mmHg @ 20°C):	Typical 0.3 kPa
Vapour Density (air = 1)	4.35 @ 15 Deg C
Boiling Point (°C):	Typical 145 - 300
Freezing/Melting Point (°C):	Data not available
Solubility in Water	Not miscible with water
Specific Gravity (g/ml @ 15°C):	0.80 Typical
Flashpoint (°C):	38 (Abel)
Explosion/Flammability Limits (%):	1.0 – 6.0
Auto Ignition Temperature (°C):	Data not available
Percent Volatiles	100

SECTION 10 STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions of use.

Conditions to Avoid: Avoid heat, sparks, open flames and other ignition sources.

Incompatible Materials: Strong oxidising agents.

Hazardous Decomposition Products: Thermal decomposition is highly dependant on conditions. A complex mixture of airborne solids, liquids, gases, including carbon monoxide, carbon dioxide and other organic compound will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11 TOXICOLOGICAL INFORMATION

HEALTH EFFECTS

Acute:

Swallowed: Expected to be of low toxicity: LD50>2000mg/kg, Rat. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Eye: Mild irritant.

Skin: Mild irritant. Prolonged contact may cause defatting of skin which can lead to dermatitis.

Inhaled: Inhalation of vapours or mists may cause irritation the respiratory system.

Chronic: Auditory system: prolonged and repeated exposures to high concentration have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss. Central nervous system: repeated exposure affects the nervous system.

SECTION 12 ECOLOGICAL INFORMATION

Ecotoxicity:

Fish	: Expected to be harmful
Aquatic Invertebrates	: Expected to be harmful
Algae	: Expected to be toxic
Microorganisms	: Expected to be Harmful
Mobility	: Floats on water
Persistence/degradability	: Readily Biodegradable. Oxidises by photo-chemical reactions in air.
Bioaccumulation	: Has the potential to bioaccumulate

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal Methods: Ensure waste disposal conforms to local waste disposal regulations.

SECTION 14 TRANSPORT INFORMATION

UN Number:	1223	Proper Shipping Name:	Kerosene
Class:	3	Subsidiary Risk:	None allocated
Packing Group:	III	Hazchem Code:	3[Y]
Special Precautions for User:	None		

Product: KEROSENE

SECTION 15 REGULATORY INFORMATION

Poisons Schedule : 5
AICS : Listed
Dangerous Goods Initial Emergency Response Guide (SA HB76:2004) : 15

SECTION 16 OTHER INFORMATION

Further Information may be obtained by contacting Recochem on (07) 3308 5200

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product.
